

SGC-14 Drive Steel Kit (#50243)



The SGC-14 Drive steel kit is designed for use with the HB90-14 Anchor Driving Hammer and is composed of the following components:

- 1 SG-14 1 1/4" Hex x 6" Shank (32mm hex x 152mm) Shank
- 1 SG-3 Radius Drive Tip 30" (76.2cm) OAL
- 2 SG_2 Drive steel extensions 33" (83.8cm) OAL
- 3 SG-4 Drive Steel Couplers
- 1 SG-X Drive steel Extractor Bar
- 1 GB-1 Carrying Bag

This is enough drive steel for normal Manta Ray installations to a depth of 7 ft. (2.1m). For greater depths more drive steel extensions and couplers may be added. The SG-X extractor bar allows the LL-1 Load Locker to be used to extract stuck drive steel)

The patented Manta Ray SG drive steel uses a partial left hand thread that allows very efficient impact energy transfer from the hammer to the anchor. All joints should be lubricated with light oil or spray lubricant prior to assembly. After installing an anchor the drive steel joints should be cleaned of dirt which will enter the couplers during driving. Failure to clean and lubricate the drive steel and couplers will result in premature failure. Drive steel parts are available separately and come in lengths of 3, 6, 8 feet (.9, 1.8, 2.4m). Medium and heavy duty couplers are also available. Contact your Manta Ray distributor.